

PRELIMINARY OPERATION MANUAL - QL DISK

```

90 IF o$ == "0" : GO TO 30
100 STOP
110 IF ERR = -7 : GO TO 200
120 PRINT "Retry"
130 GO TO 30
140 PRINT "The file does not exist."
150 GO TO 120

```

NOTE: The error code -7 corresponds to "NOT FOUND".

A table of error codes has been included in appendix A2.

4.0.0 FILES

4.1.0 Files, in general

4.1.1 OPEN_NEW

4.2.0 Written file formats

- * ASCII format
- * Internal QL format
- * Byte format

4.2.1 ASCII format

4.2.2 Internal QL format

4.2.3 Byte format

4.3.0 File opening

4.3.1 Creating a new file

Command : OPEN_NEW (**)

4.3.2 Opening a file in which alteration may occur

Command : OPEN (**)

4.3.3 Opening a file for reading only

Command : OPEN_IN (**)

4.3.4 Opening a file which may be over-written by a new file

Command : OPEN_OVER

Syntax : OPEN_OVER #ch, FLDn_filename

Parameter :

Action :

4.4.0 File closing

In general, once writing to a file has been completed by one above commands, the SuperBASIC command CLOSE is used. Where a number has been specified, the command is CLOSE #ch.

5.0.0 Random access of files

5.1.0 Random reading of files

5.1.1 ASCII format - INPUT command

Syntax : INPUT #ch, [list of variables]

Parameters : #ch :

[list of variables] : var 1, var 2 , var

NOTE: Variables are each separated by commas.