

PRELIMINARY OPERATION MANUAL - QL DISK

- Action :
- 5.4.3 Command : APPEND
 Syntax : APPEND #ch
 Parameters :
 Action :
- 6.0.0
- 7.0.0 Matrix(?) Operations
- 7.1.0 Saving
 Command : SARRAY
 Syntax : SARRAY namtab TO FLDn_filename
 Parameters : namtab = Name of the variable table or matrix(?) of the BASIC program
 Action :
 NOTE :
- 7.2.0 Loading
 Command : LARRAY
 Syntax : LARRAY FLDn_filename to namtab
 Parameters : namtab = Name of variable, table or matrix(?) of the BASIC program.
 Action :
 NOTE :
- 8.0.0 DIRECT ACCESS OF DISK SECTORS
- * The number of the drive (n) - 1 or 2
 - * The number of the side (ns) - 0 or 1
 - * The number of the track (nt) - 0 to 79
 - * The number of the sector (np) - 1 to 9
- 8.1.0 Command : RS - To read a disk sector
 Syntax : RS FLDn_,ns,nt,np,DB
 Action : To transfer 512 bytes of a disk sector; define the number of the drive (n), the number of the disk side (ns), the number of the track (nt) and the number of the sector (np) into a block of memory, beginning at address DB.
 Example : RS FLD1_,1,18,5,HEX("3E000")
- 8.2.0 Command : WS - To exclaim(?) a disk sector.
 Syntax : WS FLDn_,ns,nt,np,DB
 Action :
 Example : WS FLD1_,0,18,5,HEX("3E000")
- 9.0.0
- 10.0.0 CONTROL OF THE MULTI-TASKING ENVIRONMENT
- PRIOR Allows a change of task priority.
 ACTIV Activates an inactive task.
 SUSJOB Suspends a named active task.
 RELJOB Restarts a suspended job.
 RMVJOB Removes a named job from the list of tasks.

Screen information regarding the job list is detailed and includes: